



Grained Metallic

Code No.289

| Technical data | | |
|---|-------------|----------|
| Color: Ral colors | | |
| Gloss : Grained matte | | |
| Volume solids: 45±2% | | |
| Dilution/cleaning: 102 solvent | | |
| Theoretical Coverage: 9 sq.m/liter | | |
| Recommended layer thickness: 50 microns | | |
| Environment temperature during application: 10-30°C | | |
| Drying time: (at 20-25°C) | | |
| To touch: 15-30 minutes | | |
| To recoat: 4 hours | | |
| Final dry: 24 hours | | |
| Shelf life: (at 20-25°C) 12 months | | |
| Application | | |
| Method Application | Solvent | Dilution |
| brush/roller | 102 solvent | 0-10% |
| spray | 102 solvent | 0-20% |
| Airless spray | 102 solvent | 0-10% |
| Note concerning application | | |
| 1) Mix well prior to use and during application. 2) Do not apply at temperatures lower than 10°C. 3) Apply on the material within 4-24 hours when it is still sticky. 4) For professional use only!. | | |

| Description of the product |
|--|
| Decorative paint for direct painting over metals and rusty metals without requiring a primer in grained matte finish. Fast drying, paint is especially suited for the Israeli climate. With excellent adhesion, good weather resistance, dries quickly and protects the metal from rust. |
| Applications |
| <ul style="list-style-type: none">• Decorative metallic structures (fences and guardrails)• For direct application on rust, without any need for primer• Handrails• Iron fences• Elevators• Doors• Handrails• bars• Gates• Metal lintels• Can be painted directly on galvanized metal, steel or• Black tin (after preparing a suitable area). |
| Special properties |
| <ul style="list-style-type: none">• Fast drying• Aesthetic decorative effect |
| Package |
| 4.5 Lit , 18 Lit |